

PRIMER VL 2K

PRODUCT

Primer VL 2K is a liquid, two-component, polyurethane primer for improving the adhesion of several ELASTOTET products on porous substrates. **PRIMER VL 2K** does not contain any solvents.

APPLICATIONS

- Pretreatment of mineral substrates, such as brickwork, concrete and lightweight concrete.
- Pretreatment of wooden substrates.
- Flooring applications in combination with polyurethane coatings.
- Primer for Polyurethane roof coatings (i.e. **LASTOFLEX-PU**) or Polyurethane sealants (i.e. **ELASTOSEAL-PU**) when applied on asphalt or asphaltic membranes.

METHOD OF USE

Substrates should be clean, free from dust and grease. Keep the packaging well closed until the moment of use. Mix the two components well and apply by brush or roller. Use always a clean brush for the application of **Primer VL 2K**. Apply the primer to the adhesion surface only in such a way, that the primer forms a continuous coat or film. The primer should be applied in a thin coat. Do not apply **Primer VL 2K** more than 200 gr/m². Do not mix more primer than can be applied within the pot life of the product. Avoid contact with the cleaned and primed surfaces because greasy fingers can cause a bad adhesion.

TECHNICAL DATA

Dry contents : 100%
Specific gravity : 1.08 g/ml
Mixing Ratio (A : B) : 2 : 1
Pot Life at 23 °C : 25 minutes
Packaging 10 kg



COVERAGE

The coverage depends on the type of substrate and will be between 100 and 200 gr/m².

STORAGE STABILITY

Primer VL 2K can be stored for 12 months in a closed (unopened) container in a dry place at temperatures between +5°C and +30°C.

WARNING TO USERS

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELASTOTET GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELASTOTET is at their disposal to supply any additional information.